

15 GAUGE



Type of use

Thanks to its technical characteristics, this glove is suitable for all light and medium works in wet and/or fat/oily conditions, requiring good dexterity and protection against mechanical risks in particular abrasion: automotive assembly, precision engineering, industrial maintenance, repair of mechanical parts, electronic industry, small parts assembly ...

Technical features

- ✓ **Construction:** knitted seamless pattern.
- ✓ **Gauge:** 15.
- ✓ **Materials:**
 - Liner in polyamide and Elastane. Elastic knitted wrist.
 - Coating: special nitrile foam; open back version. Nitrile dots on palm.
- ✓ **Colour:** black coating, grey liner.
- ✓ **Sizes:** 7, 8, 9, 10.
- ✓ **Packing:** - carton of 100 pairs.
- bundle of 10 pairs.



Learn more: www.kerckhaert.com

Main advantages

- ✓ The gloves are machine knitted liners made from Polyamide / Elastane which gives good fit and sensitivity, superior comfort and dexterity.
- ✓ Soft, foam nitrile coating on palm and polymer dots not only enhances protection but it also provides good wet grip by channeling away excess fluid from the surface.
- ✓ Glove provides good protection in dry and wet handling conditions.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The back of the glove uncoated allowing the hand to breathe.



Conformity

This glove has been tested according to the european standard **EN388: 2003** against mechanical risks (intermediate design). It complies with European Directive **89/686/EEC** on Personal Protective Equipment (**PPE**). EC type examination certificate issued by the **SATRA**, notified body **n°0321**.



EN388: 2003. Mechanical data. Information on levels	Level 1	Level 2	Level 3	Level 4	Level 5	NYMFIT00 Levels obtained	EN388: 2003
Abrasion resistance (number of cycles)	100	500	2000	8000	-	4	<p>4 1 4 1</p>
Blade cut resistance (indice)	1,2	2,5	5,0	10,0	20,0	1	
Tear resistance (in newtons)	10	25	50	75	-	4	
Puncture resistance (in newtons)	20	60	100	150	-	1	

